

## MOTIP Brake Caliper Paint

Ord.-no.: look at ordering information

## Technical Information



Paint your brake calipers in a new colour with MOTIP Brake Caliper Paint. Use the paint to highlight brake pads in the colours yellow, red, blue and silver. The paint has good filling properties and a lasting gloss. The paint is scratch free, shock proof and resistant to petrol, chemicals and the weather, and is rust and dirt preventive.

### Quality & properties

- Good filling property
- Resistant to petrol, chemicals and weather influences
- Lasting gloss
- Scratch free and shock proof
- Corrosion preventive
- Dirt preventive
- Non-fading (UV-resistant)
- Excellent adhesion

### Physical & chemical data

- Base: Alkyd resin
- Colourname:
  - ◊ silver
  - ◊ yellow
  - ◊ red
  - ◊ blue
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 4 brake pads
- Dry to touch: 180 min
- Dust dry: 20 - 40 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: Brake pads
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Relative density: 0.7 g/ml
- Temperature Resistance: – 110-150 °C
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: De surface should be clean, dry and free of fat. Remove loose old lacquer and rust and then sand. Apply a layer of MOTIP primer. After drying, sand the base layer (grain 600).
- The surface should be clean, dry and free of fat. The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample.
- Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline

