

MOTIP Silicone Spray

Technical Information



Protect and lubricate rubber parts against freezing, drying out and plastic parts from creaking and squeaking with MOTIP Silicone Spray. Silicone spray is water-repellent, pH-neutral and resistant to the weather and weak acids and bases. Silicone spray has outstanding mechanical and thermal stability. MOTIP Silicone Spray has a directed jet-spray and is resistant to temperatures of - 50°C up to + 200°C.

Ord.-no: 090107, 290107, 000562

Quality & properties

- Prevents freezing and drying out of rubber parts
- Outstanding mechanical and thermal stability
- Prevents creaking and squeaking of plastic parts
- Water-repellent
- Excellent adhesion
- Resistant to weather influences
- Directed jetspray
- Resistant to weak acids and bases

Physical & chemical data

- Base: Polydimethylsiloxane
- Colourname: no colour
- Surfaces: Door rubbers, Creaking plastic parts, Dashboards, Bumpers, Sunshine roofs Rails (caravan, blinds), Sliding doors, Saw blades, Remove agents for moulds
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - 500 ML
 - 200 ML
 - 400 ml

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply silicone spray in a thin layer. Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.