

MOTIP Rubber & Plastic Conditioner

Technical Information



Maintain the rubber and plastic parts of your car with MOTIP Rubber & Plastic Conditioner. Conditions rubber parts and restores the gloss and intensifies the colour of plastic parts. Rubber & Plastic Conditioner gives a lasting gloss and is very suitable for removing the residue from polishes. Rubber & Plastic Conditioner prevents freezing and drying out of rubber parts and protects against bad weather. MOTIP Rubber & Plastic Conditioner contains silicones and is pH-neutral.

Ord.-no: 000709

Quality & properties

- User-friendly
- Lasting gloss
- Restores the colour
- To remove residue of polishes
- Contains silicones
- Prevents freezing of rubber parts
- Prevents drying out of rubber parts
- Protects against weather influences
- pH-neutral

Physical & chemical data

- Base: Vaseline and high viscous silicone oil
- Colourname: no colour
- Surfaces: Rubbers and other plastic parts of the car
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 600 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature. Best processing temperature 5 to 30°C.
- Before use, shake the aerosol.
- The surface must be clean and dry.
- Apply Plastic and Rubber Conditioner in a thin, equal layer and polish with a soft cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.